<u> 30th St.</u> 3000 N OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION 25 TOWNSHIP.

DATE: -6-27-04 R
PARTY CHIEF: Wilcoxen 16 $\frac{1}{11}$ RANGE $\frac{4}{04}$ Re-set AVE CREW: TYPE OF MARKER: Harrison METHOD OF ESTABLISHMENT: ____County: 8-27-96 Shadel IN. S.P.C. E ZONE NAD 16042501 506609.0490(m) NAME: Ν: 67549.3470(m) E: 1. 5 Aive 30th Street 3000 N Shadeland 30.75 Section Line

Original post set 1920 by Hendricks with witness: 14" beech S 4 E 29 links; 15" burr oadk N 21 W 20 links per Marion County Atlas pg. 11. Hosbrook 7-21-1849 called rock set no witness per Warren Township Legal Book pg. 3. Fatout 4-27-1882 called rock found with witness: 15" poplar N 60 W 50 links; 20" oak S 47 W 140 links per Warren Township Legal Survey Book pg. 4. Woerner 6-18-48 called brass pin. Monroe 3/58 called same. Day 5-21-70 called brass plug. Wilcoxen 8-27-95 called a brass plug. Excavated 8/96 by Wilcoxen and set Harrison. Re-tied 6-27-04 by Wilcoxen.

100	772001	
REF.	DISTANCE	DESCRIPTION
1.	60.42	PK nail W PwP#1-448 A 4"up
2.	68.26	Cut 'x' SW bolt of aluminum pole base
3.	30.75	Cut 'x' W-end of median
4.	81.27	PK nail SW PwP#39-448 B 12"up
5.	53.34'	Cut 'x' S-end of median